

Formulas:

$T_3 = 273.16K = 0.01^\circ C$; water freezes/boils at $T = 0^\circ C = 32^\circ F / T = 100^\circ C = 212^\circ F$
 $1cal = 4.1868J$; $N_A = 6.02 \times 10^{23}$

Thermal expansion: $\Delta L = L\alpha\Delta T$; $\Delta V = V\beta\Delta T$; $\beta = 3\alpha$

Heat capacity and specific heat: $Q = C\Delta T$; $Q = cm\Delta T$

Heat of vaporization, fusion: $Q = L_v m$; $Q = L_f m$

First law of thermodynamics: $\Delta E_{int} = Q - W$; $dE_{int} = dQ - dW$; $W = \int_{V_i}^{V_f} p dV$ work

Conduction: $P_{cond} = \frac{Q}{t} = kA \frac{T_H - T_L}{L}$; $R = \frac{L}{k}$ k,R=thermal conductivity, resistance

Radiation: $P_{rad} = \sigma \epsilon A T^4$; $\sigma = 5.67 \times 10^{-8} W / m^2 K^4$ $\epsilon = 1$ for black body

Ideal gas: $PV = nRT = NkT = nN_A kT$; $R = 8.31 J/molK$; $k = 1.38 \times 10^{-23} J / K$

Pressure: $P = \frac{Nm}{3V} (v^2)_{avg}$ Kinetic energy: $K_{avg} = \frac{1}{2} m (v^2)_{avg} = \frac{3}{2} kT$

Internal energy: $E_{int} = NK_{avg}$; $C_V = \frac{3}{2} R$ for monoatomic gas; $C_P = C_V + R$

C_V, C_P = molar heat capacity at constant volume, pressure

$C_V = \frac{f}{2} R$ for polyatomic gases with f degrees of freedom per molecule

Adiabatic expansion of ideal gas: $PV^\gamma = const$, $TV^{\gamma-1} = const$; $\gamma = C_P / C_V$

Distribution of molecular speeds: $P(v) = 4\pi \left(\frac{m}{2\pi kT}\right)^{3/2} v^2 e^{-mv^2/(2kT)}$

Velocity distribution: $F(v_x, v_y, v_z) = f(v_x)f(v_y)f(v_z)$, $f(v_x) = \left(\frac{m}{2\pi kT}\right)^{1/2} e^{-mv_x^2/(2kT)}$

Mean free path: $\lambda = 1/(\sqrt{2}\pi d^2 N / V)$, d=diameter ; $v_{rms} = \sqrt{(v^2)_{avg}}$

Entropy: $dS = dQ / T$ in a reversible process. S is a function of state. $\Delta S = \int_i^f dQ / T$

$\Delta S \geq 0$ for a closed system. = if reversible process, > if irreversible process

Ideal gas: $S(T, V) = nR \ln V + nC_V \ln T + const$

Heat engine: $\epsilon = \frac{|W|}{|Q_H|}$; Carnot engine: $\epsilon = 1 - \frac{|Q_L|}{|Q_H|} = 1 - \frac{T_L}{T_H}$

Refrigerator coefficient of performance $K = \frac{|Q_L|}{|W|}$; Carnot refrigerator $K_C = \frac{T_L}{T_H - T_L}$

Statistical view of entropy: $S = k \ln W$; $W = N! / (n_1! n_2! \dots)$; $N! \approx N(\ln N) - N$

Fluids: $\rho = m / V$, $p = F / A$, $1 \text{ atm} = 1.01 \times 10^5 \text{ Pa} = 760 \text{ torr}$

Fluid at rest: $p_2 + \rho g y_2 = p_1 + \rho g y_1$; gauge pressure = $p - p_{\text{atmospheric}}$

Pascal's principle: $\Delta p = F_1 / A_1 = F_2 / A_2$

Archimedes principle: buoyant force $F_b = m_{\text{fluid}} g$

Continuity equation: volume flow rate = $R_V = Av = \text{a constant}$

Bernoulli equation: $p + \frac{1}{2} \rho v^2 + \rho g y = \text{a constant}$

Oscillations: simple harmonic motion: $x(t) = x_m \cos(\omega t + \phi)$; $\omega = 2\pi f = 2\pi / T$

spring: $F = -kx$, $\omega = \sqrt{k / m}$, energy: $E = U + K = \frac{1}{2} k x_m^2$; $U = \frac{1}{2} k x^2$, $K = \frac{1}{2} m v^2$

torsion pendulum: $\tau = -\kappa \theta$, $\omega = \sqrt{\kappa / I}$; simple pendulum: $\omega = \sqrt{g / L}$

physical pendulum: $\omega = \sqrt{mgh / I}$; $I = I_{CM} + mh^2 = \int r^2 dm$

Damped shm: $F_d = -bv$, $x(t) = x_m e^{-bt/2m} \cos(\omega' t + \phi)$, $\omega' = \sqrt{\omega^2 - (b/2m)^2}$

Forced oscillations: $F_f = f \cos(\omega_d t)$, $x(t) = x_m \cos(\omega_d t + \phi)$; resonance: $\omega_d = \omega$

$$x_m = (f / m) / \sqrt{\omega_d^2 - \omega^2 + b^2 \omega_d^2 / m^2}, \tan \phi = (b / m) \omega_d / (\omega_d^2 - \omega^2)$$

Waves:

$y(x, t) = y_m \sin(kx - \omega t)$; $\omega = 2\pi f = 2\pi / T$; $k = 2\pi / \lambda$; $v = \omega / k = \lambda f = \lambda / T$

string: $v = \sqrt{\tau / \mu}$; power: $P_{\text{avg}} = \frac{1}{2} \mu v \omega^2 y_m^2$

interference: $y'(x, t) = [2y_m \cos \frac{1}{2} \phi] \sin(kx - \omega t + \frac{1}{2} \phi)$

standing waves: $y'(x, t) = [2y_m \sin(kx)] \cos \omega t$; resonance: $f = \frac{v}{\lambda} = n \frac{v}{2L}$

speed of sound: $v = \sqrt{\frac{B}{\rho}}$; $B = -V \left(\frac{\partial P}{\partial V} \right)_S$; ideal gas: $B = \gamma P$

$s = s_m \cos(kx - \omega t)$; $\Delta p = \Delta p_m \sin(kx - \omega t)$; $\Delta p_m = v \rho \omega s_m$

interference: $\phi = \frac{\Delta L}{\lambda} 2\pi$; constructive $\phi = 2\pi m$, destructive $\phi = \pi(2m + 1)$

sound intensity $I = \frac{P}{A} = \frac{1}{2} \rho v \omega^2 s_m^2 = \frac{P_s}{4\pi r^2}$; decibels $\beta = (10 \text{ dB}) \log \frac{I}{I_0}$, $I_0 = 10^{-12} \text{ W} / \text{m}^2$

pipes: $f = \frac{nv}{2L}$, $n = 1, 2, 3$ or $f = \frac{nv}{4L}$, $n = 1, 3, 5$; beats $f_{beat} = f_1 - f_2$

Doppler: $f' = f \frac{v \pm v_D}{v \pm v_s}$; shock wave $\sin \theta = \frac{v}{v_s}$