

Formulas:

$$F = k \frac{q_1 q_2}{r^2} \quad \text{Coulomb's law} ; k = \frac{1}{4\pi\epsilon_0} = 8.99 \times 10^9 \text{ N} \cdot \text{m}^2 / \text{C}^2 ; \epsilon_0 = 8.85 \times 10^{-12} \text{ C}^2 / \text{Nm}^2$$

$$\text{Electric field: } \vec{E} = \frac{q}{4\pi\epsilon_0 r^2} \hat{r} = \frac{kq}{r^2} \hat{r} ; \quad \vec{E}(\vec{r}) = k \int \rho(\vec{r}') \frac{\vec{r} - \vec{r}'}{|\vec{r} - \vec{r}'|^3} d^3 r' ; \quad \vec{F} = q_0 \vec{E}$$

$$\text{Linear, surface, volume charge density: } dq = \lambda dl \quad , \quad dq = \sigma da \quad , \quad dq = \rho dv$$

$$\text{Electric field of infinite: line of charge: } E = \frac{\lambda}{2\pi\epsilon_0 r} ; \quad \text{sheet of charge: } E = \frac{\sigma}{2\epsilon_0}$$

$$\vec{\nabla} \times \vec{E} = 0 \quad (\text{electrostatics})$$

$$\text{Gauss law: } \Phi = \oint \vec{E} \cdot d\vec{a} = \frac{q_{enc}}{\epsilon_0} = \frac{1}{\epsilon_0} \int d^3 r \rho(\vec{r}) ; \quad \Phi = \text{electric flux}$$

$$\text{Energy: } U = k \frac{q_1 q_2}{r_{12}} \quad U = \frac{\epsilon_0}{2} \int E(\vec{r})^2 d^3 r \quad \text{Work: } W = \int \vec{F} \cdot d\vec{s}$$

$$\text{Electric potential: } \phi(P_2) - \phi(P_1) = - \int_{P_1}^{P_2} \vec{E} \cdot d\vec{s} \quad \phi(\vec{r}) = \frac{1}{4\pi\epsilon_0} \int d^3 r' \frac{\rho(\vec{r}')}{|\vec{r} - \vec{r}'|}$$

$$\text{Point charge: } \phi(\vec{r}) = \frac{1}{4\pi\epsilon_0} \frac{q}{r} \quad \text{Dipole: } \phi(r, \theta) = \frac{p \cos \theta}{4\pi\epsilon_0 r^2}$$

$$U = \frac{1}{2} \int \rho \phi d^3 r \quad \vec{E} = -\vec{\nabla} \phi \quad ; \quad \vec{\nabla} \cdot \vec{E} = \frac{\rho}{\epsilon_0} \quad ; \quad \vec{\nabla} \times \vec{E} = 0$$

$$\text{Capacitors: } Q = C\phi \quad , \quad U = \frac{Q^2}{2C} ; \quad \text{Planar: } C = \frac{\epsilon_0 A}{s} \quad \text{Spherical: } C = 4\pi\epsilon_0 R$$

$$I = \int \vec{J} \cdot d\vec{a} \quad , \quad I = \frac{dQ}{dt} \quad , \quad \vec{J} = nq\vec{u} \quad ; \quad \text{div} \vec{J} = -\frac{\partial \rho}{\partial t} \quad ; \quad \text{Power: } P = I^2 R \quad ; \quad P = \epsilon I$$

$$V = IR ; \quad \vec{J} = \sigma \vec{E} ; \quad \vec{E} = \rho \vec{J} ; \quad R = \rho \frac{L}{A} ; \quad \sigma = \frac{ne^2 \tau}{m_e} ; \quad Q(t) = C\epsilon(1 - e^{-t/RC}) ; \quad Q(t) = Q_0 e^{-t/RC}$$

$$\text{Lorentz force: } \vec{F} = q(\vec{E} + \vec{v} \times \vec{B}) ; \quad \text{force on wire: } d\vec{F} = Id\vec{\ell} \times \vec{B} \quad ; \quad \text{solenoid: } B = \mu_0 nI$$

$$\text{Stokes' theorem: } \oint_C \vec{F} \cdot d\vec{s} = \int_S \vec{\nabla} \times \vec{F} \cdot d\vec{a} \quad ; \quad \text{vector potential: } \vec{\nabla} \times \vec{A} = \vec{B}$$

$$\text{Ampere's law: } \oint_C \vec{B} \cdot d\vec{s} = \mu_0 I_{enc} = \mu_0 \int_S \vec{J} \cdot d\vec{a} \quad ; \quad \vec{\nabla} \times \vec{B} = \mu_0 \vec{J} ; \quad \vec{\nabla} \cdot \vec{B} = 0$$

$$\text{Field of a wire: } B = \frac{\mu_0 I}{2\pi r} \hat{\theta} \quad ; \quad \text{Force between wires: } F = \frac{\mu_0 I_1 I_2 \ell}{2\pi r} \quad ; \quad \text{cyclotron: } \omega = \frac{qB}{mc}$$